

ISO9001
ISO14001
ISO13485
CERTIFIED



Pihsiang offers you a complete mobility package incorporating world class quality, design, reliability and service.

A WORLD PATENTED NEW MODEL TE-787NA

SPECIFICATION

Overall Dimensions: L ¹ x W x H	mm(in)	1020(37) x 430(17) x 870(34)
Number, Size of Tires	Front	2 , 7"
	Rear	2 , 8"
Suggested User Weight (on the level road)	kg(lb)	Max. 90 (200)
Total Weight (w/ batteries,basket,seat)	kg(lb)	33.4(73.5)
Battery Weight	kg(lb)	2X4.5(2X10)
Weight of Heaviest Part	kg(lb)	11.2(24.6)
Carrying Weight with Full Assembly (w/o batteries & seat)	kg(lb)	18.0(39.6)
Battery Capacity	_V_Ah x Pcs	12V 12Ah x 2
Charger		On Board
Motor Output Power	W(hp)	336(0.45)
Maximum Speed	km/hr(mph)	6(3.75)
Safe Climbing Angle (based on user weight of 90kg/200lb)	°(%)	12 (21)
Range ² (per charge)	km(mile)	24(15)
Turning Diameter	mm(in)	Turn on a dime
Detachable Chassis	Y/N	Y(& Stretchable)
Handle Bar Type	Type	T

All specification subject to change without prior notice.

Ver : 2002.09.09/A7

¹Include the Anti-Tip wheel.

²The actual driving range varies with the factors shown as below.

- (1) the weight of occupant
- (2) ground surface
- (3) battery conditions
- (4) type of charger
- (5) ambient temperature
- (6) the way of driving
- (7) etc.

